

Disclaimer:

This English translation is produced by machine translation and may contain errors. The JPO, the INPIT, and those who drafted this document in the original language are not responsible for the result of the translation.

Notes:

1. Untranslatable words are replaced with asterisks ("**").
2. Texts in the figures are not translated and shown as it is.

Translated: 22:05:01 JST 10/13/2009

Dictionary: Last updated 08/17/2009 / Priority: 1. information communication technology (ICT) / 2. Electronic engineering / 3. Mathematics/Physics

FULL CONTENTS

[Claim(s)]

[Claim 1]A laser reflow jig having a slit and a printed circuit board which were hollowed so that a sequence of putt might be surrounded, a guide which positions a surface-mount type connector, and a pin on the occasion of soldering by laser of a surface-mount type connector.

[Detailed Description of the Invention]

[0001]

[Industrial Application]When this invention carries out laser soldering of the electronic parts mounted in the printed circuit board etc., especially, it positions a printed circuit board, the putt of electronic parts, and a lead, and relates to the art which does and solders damage.

[0002]

[Description of the Prior Art]As conventional technology about soldering of laser, the art indicated to JP,H01-84888,U etc. is known, for example.

[0003]This conventional technology is having the opening hollowed so that it might leave a fixed interval to the sequence of the putt for surface-mount mold part article loading and the sequence of putt might be surrounded, and prevents damage to a printed circuit board.

[0004]

[Problem to be solved by the invention]However, said conventional technology has a problem of the damage to a surface-mount mold part article, or the soldering poor frequent occurrence by the energy scarcity of laser.

[0005]There is the purpose of this invention in providing the laser reflow jig which can position easily the putt of a printed circuit board, and the lead of a surface-mount mold part article while solving the problem of said conventional technology.

[0006]

[Means for solving problem]According to this invention, said purpose is attained by surrounding the whole surface-mount mold part article, and providing a slit in the putt upper part of a printed circuit board, and positioning a surface-mount mold part article by a guide, and positioning a printed circuit board by a pin.

[0007]

[Function]With the laser reflow jig by this invention, irradiation of the laser beam to the surface-mount mold part

article at the time of laser soldering can be prevented, and the function which can be positioned easily can be supplied also in positioning of putt and a component lead.

[0008]Thereby, damage to a surface-mount mold part article can be prevented, and improvement in soldering quality can be obtained.

[0009]

[Working example]Hereafter, Drawings explain one embodiment of the laser reflow jig by this invention in detail.

[0010]As shown in drawing 1, the surface-mount type connector 9 is arranged in the upper part of the printed circuit board 1. The component lead 10 is fixed to both the sides of the surface-mount type connector 9, and Lead Kushva 11 is arranged at the tip of the component lead 10. The upper part of the surface-mount type connector 9 is equipped so that the laser reflow jig 1 may cover and hang. As shown in drawing 2 and drawing 3, as for the laser reflow jig 1, the opening of the slit 2 is carried out to the upper part of the putt 8, and the guide 3 is arranged in the pin 4 and its this side at both the sides of the longitudinal direction.

[0011]Next, operation of one embodiment by the above-mentioned composition is explained.

[0012]The surface-mount type connector 9 is mounted in the upper part of the printed circuit board 6. The upper part is equipped with the laser reflow jig 1. The surface-mount type connector 9 positions by the guide 3 of the laser reflow jig 1, and the component lead 10 of the surface-mount type connector 9 and the putt 8 of the printed circuit board 6 are positioned by inserting the pin 4 in the location hole 7. Next, the component lead 10 and the putt 8 are irradiated with the optimal racer light 5, without irradiating a laser beam and irradiating the surface-mount type connector 9 and Lead Kushva 11 from the upper part of the laser reflow jig 1.

[0013]

[Effect of the Invention]It will be as follows if the effect acquired by this invention is explained.

[0014]Namely, in the laser reflow jig used when the printed circuit board by laser and a surface-mount type connector solder, It is a thing possessing the positioning function of the optimal slit for soldering of a laser beam, and a printed circuit board and a surface-mount type connector, and the improvement in soldering quality and damage to a surface-mount type connector can be prevented.

[Brief Description of the Drawings]

[Drawing 1]It is a front sectional view showing one embodiment of the laser reflow jig of this invention.

[Drawing 2]It is an upper surface figure showing one embodiment of the laser reflow jig of this invention.

[Drawing 3]It is a side sectional view showing one embodiment of the laser reflow jig of this invention.

[Explanations of letters or numerals]

1 -- Laser reflow jig

2 -- Slit

3 -- Guide

4 -- Pin

5 -- Laser beam

6 -- Printed circuit board


7 -- Location hole

8 -- Putt

- 9 -- Surface-mount type connector
- 10 -- Component lead
- 11 -- Lead Kushva


[Drawing 1]

[3x] 1



[Drawing 2]

[3x] 2



[Drawing 3]

[3x] 3

